RR EC 200




SVR EC 200




SlimVent – Slimline EC space saver w/ retractable motor-impeller unit.

Dimensions RR EC 200



Dim. in mm

Dimensions SVR EC 200



Dim. in mm

Energy-saving EC circular duct fans for the delivery medium and small air volumes against high resistances.
Specifically designed for direct insertion in duct systems. High pressure performance for overcoming friction losses, deflection losses and aggregate resistances.
For various applications in commercial, industrial and residential areas.

Special features

- ☐ Highly efficient EC motor for low operating costs.
- ☐ Low space requirement and installation costs due to linear throughflow.
- ☐ No need for elaborate deflectors.
- ☐ Connectors on inlet and outlet side correspond to standard duct Ø.
- ☐ Performance adjustment through 100% speed control.
- ☐ Can be used in any position.
- ☐ Wide range of accessories.
- ☐ Aerodynamically optimised casing design.

Common features RR EC and SVR EC

Drive
Energy-saving, speed-controllable EC external rotor motor in protection category IP44 a high level of efficiency. Maintenance-free and ball bearing mounted.

Motor protection
Integrated electronic temperature monitoring system for EC motor and electronics.

Installation
No restrictions in any position (horizontal, vertical, diagonal) through corresponding installation for supply or extract ventilation. Installation in duct system, preferably away from the room to be ventilated for less noise.

Description RR EC

Casing
Made of galvanised steel sheet, robust for harsh operating conditions. Inlet and outlet side connection dimensions correspond to standard duct Ø.

Power control
Continuously variable speed control with internal (delivery) or external potentiometer or continuously variable speed control with universal control system (see table). Performance levels are shown in the performance curve as an example.

Electrical connection
Terminal box (IP54) on outside of casing.

Impeller
Centrifugal, with backward curved blades made of plastic. Dynamically balanced together with motor for low-noise operation, high level of efficiency.

Protection category
Protection category IP54 through inlet and outlet-side installation in a duct system which prevents the ingress of rainwater.

Description SVR EC

Casing
Flat casing in compact design made of galvanised steel sheet. Connectors and lip seal on inlet and outlet side for standard duct Ø.
The retractable motor-impeller unit allows inspection and cleaning without dismantling components. The swivelling range must be considered for the inspection opening.

Power control
Continuously variable speed control with internal (delivery) or external potentiometer or continuously variable speed control with universal control system (see table). Performance levels are shown in the performance curve as an example.

Electrical connection
Terminal box (IP54) on external cable.

Impeller
Energy-saving centrifugal impeller with backward curved blades made of high-quality plastic. Dynamically balanced together with motor for low-noise operation.

Protection category
IP44 with connected duct system.

Noise
The total level and range are specified above the performance diagram for:
- ☐ Case-radiated sound power
- ☐ Inlet side sound power
- ☐ Outlet side sound power.


The case-radiated noise as sound pressure at 1 m (free field conditions) is also specified in the type table and the table below the performance curve.

Type	Ref. no.	Connection Ø	Flow rate Free blowing	Rated speed	Sound press. case radiation	Power consum.	Current consum.	Wiring diagram	Max. air flow temp.	Wgt net aprx.	Universal control system		Speed potentiometer flush-mount.		Speed potentiometer surf-mount.	
		mm	V̇ m³/h	min⁻¹	dB(A) in 1 m	kW	A	No.	+ °C	kg	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.
Type RR EC, Single-phase alternating current, 230 V, 50/60 Hz, EC motor, IP44																
RR EC 200 A	06121	200	985	2890	44	0.12	1.00	979	60	3.4	**EUR EC**[1)2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735
RR EC 200 B	05786	200	1130	3200	47	0.17	1.37	979	60	4.0	**EUR EC**[1)2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735
Type SVR EC, Single-phase alternating current, 230 V, 50/60 Hz, EC motor, IP44																
SVR EC 200 A	03310	200	850	2900	50	0.12	1.02	979	60	7.4	**EUR EC**[1)2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735
SVR EC 200 B[3)]	02539	200	980	2890	53	0.15	1.19	979	60	7.4	**EUR EC**[1)2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735

[1)] Multiple EC fans can normally be connected. [2)] alternative electronic diff. pressure/ temperature controller (EDR/ETR, No. 01437/01438) or three level speed switch (SU/SA, No. 04266/04267), see accessories.
[3)] Performance diagram at www.HeliosSelect.de

Performance curves RR EC 200 A


Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	52	30	44	47	43	44	43	31
L_{WA}	Inlet side	dB(A)	75	63	68	70	66	67	63	55
L_{WA}	Outlet side	dB(A)	75	65	67	69	66	70	65	56



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	2900	985	85	0.70	44	0.31
8	2550	860	55	0.50	41	0.23
6	1960	670	30	0.25	34	0.16
4	1360	460	15	0.12	28	0.12

Performance curves RR EC 200 B


Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	55	28	38	51	49	47	45	33
L_{WA}	Inlet side	dB(A)	77	66	69	73	69	68	66	60
L_{WA}	Outlet side	dB(A)	78	67	72	70	69	71	68	60



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	3430	1130	130	1.1	47	0.41
8	2990	980	90	0.76	44	0.33
6	2260	740	40	0.37	37	0.19
4	1510	500	20	0.16	30	0.14


Performance curves SVR EC 200 A

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	58	41	51	56	48	46	40	31
L_{WA}	Inlet side	dB(A)	76	66	68	73	66	63	63	53
L_{WA}	Outlet side	dB(A)	80	66	70	77	70	71	67	56



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	2900	850	115	0.92	50	0.48
8	2550	700	75	0.65	49	0.38
6	1960	570	35	0.32	42	0.22
4	1360	390	15	0.14	32	0.14

Accessories



Pipe clamp connectors
BM 200 Ref. no. 05078
For structure-borne noise-free connection of fan and piping and for suspension (1 set = 2 pcs). Mount ventilation duct and fan connector at a distance and fold sleeve over during installation.



Mounting bracket for RR EC
MK 4 Ref. no. 05824



External wall shutter
VK 200 Ref. no. 00758
Made of plastic, light grey.

External wall cover grille
RAG 200 Ref. no. 00750
Made of plastic, light grey.

Protection grille
SGR 200 Ref. no. 05066
For inlet and outlet side installation. Made of galvanised steel.



Duct shutter
RSK 200 Ref. no. 05074
Automatic, made of metal.



Flexible cross talk silencer
FSD 200 Ref. no. 00679
Made of aluminium pipe with double-sided plug-in connectors. Sound insulation lining 50 mm thick, installation length 1 m.



Air filter box
LFBR 200 Coarse 70%* 08579
LFBR 200 ePM1 50%* 08533
Air filter with large surface area, for installation in pipeline.



Electric heating element
EHR-R 1.2/200 1.2 kW No.09436
EHR-R 2/200 2.0 kW No.09437
EHR-R 5/200 5.0 kW No.08711
– with integrated temp. control
EHR-R 5/200 TR 5.0 kW No.05295
Room or duct sensor (TFK/TFR, Accessories) required.



Temperature control system for electric heating element EHR-R
EHS Ref. no. 05002



Warm water heating element
WHR 200 Ref. no. 09482
Compact heat exchanger for installation in duct system.



Temperature control system for warm water heating element
WHST 300 T38 Ref. no. 08817

* See product page 486 for detailed description.