
GB EC 400






Any installation position and location due to five possible outlet directions.

EC

GB EC 400 T120






For the delivery of contaminated, humid and hot air up to max. 120 °C. Motor located outside of air flow.


T120 EC

Dimensions GB EC 400



Dim. in mm

Dimensions GB EC 400 T120



Dim. in mm

Special features of the GB EC T120 series

- Designed for the delivery of contaminated, humid and hot air up to max. 120 °C, e.g. as an extract air fan in commercial kitchens and many process technology applications.
- Motor located outside of air flow.
- Thermally insulated partition between motor and impeller, made of galvanised steel sheet, with 20 mm thick, non-flammable mineral wool.
- Complete motor-impeller unit can be removed without dismantling the system components.
- Inspection cover with handle, easily removable for cleaning and maintenance.
- Condensate tray with condensate drain as standard. Hole provided for rain drain (accessories) for outdoor installation.

- **Installation**
  Installation position with condensate drain below. Flexible installation due to three possible centrifugal outlet directions of the outlet fitting. Protected outdoor installation possible with weather protection cover and grille (accessories).

- **Electrical connection**
  Standard terminal box (IP54) directly to the commutation electronics.

Special features of the GB EC series

Any installation position and flexible installation due to five possible outlet directions of the outlet fitting. The wall bracket (accessories) must be used for wall installation. Protected outdoor installation possible with weather protection cover and grille (accessories).

- **Electrical connection**
  Standard terminal box (IP54) mounted to external cable.

Description for both series

- **Casing**
  Self-supporting frame construction made of aluminium hollow profiles. Double-walled, 20 mm thick side panels made of galvanised steel sheet, sound and heat insulated by non-flammable mineral wool lining.
  Nozzle on inlet side for optimal inflow as well as connectors and flexible connecting sleeve (for the respective max. permissible air flow temperature) for duct connection. Moulded part (square to round) on outlet side for low-loss outflow and flexible connecting sleeve to prevent structure-borne noise transmission. Simple positioning with standard crane hook.

- **Impeller**
  Free-running high performance centrifugal impeller made of aluminium, directly driven. Energy-efficient with low noise emission. Dynamically balanced together with the motor in accordance with DIN ISO 21940-11 – quality grade 2.5.

- **Drive**
  Energy-saving, speed-controllable EC external rotor motor in protection category IP54 with a high level of efficiency. Maintenance-free and ball bearing mounted.


- **Motor protection**
  Integrated electronic temperature monitoring system for EC motor and electronics.

Type	Ref. no.	Connection Ø	Flow rate free blowing	Rated speed	Case-rad. sound pressure	Power consumption	Current consumption	Wiring diagram	Max. air flow temp.	Weight net aprx.	Universal control system		Speed potentiometer Flush-mounted		Speed potentiometer Surface-mounted	
		mm	V̇ m³/h	min⁻¹	dB(A) in 4m	kW	A	No.	+ °C	kg	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.
Alternating current, 1~, 230 V, 50/60 Hz, EC motor, protection category IP44																
GBW EC 400 A	05817	400	4050	1200	36	0.34	1.52	973	50	43.0	**EUR EC**[1) 2)]	01347	**PU 24**[1)]	01736	**PA 24**[1)]	01737
GBW EC 400 B	05810	400	5160	1500	37	0.62	2.80	973	50	46.0	**EUR EC**[1) 2)]	01347	**PU 24**[1)]	01736	**PA 24**[1)]	01737
T120 **Alternating current, 1~, 230 V, 50/60 Hz, EC motor, protection category IP54**																
GBW EC 400 T120	06453	400	4730	1320	43	0.43	1.80	1223.1	120	60.0	**EUR EC**[1) 2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735
T120 **Three-phase current, 3~, 400 V, 50/60 Hz, EC motor, protection category IP54**																
GBD EC 400 T120	06454	400	5410	1500	46	0.62	1,20	1214.1	120	60.0	**EUR EC**[1) 2)]	01347	**PU 10**[1)]	01734	**PA 10**[1)]	01735

1) Multiple EC fans can normally be connected. 2) Alternative electronic diff. pressure/temperature controller (EDR/ETR, No. 01437/01438) or three level speed switch (SU/SA, No. 04266/04267).

Performance curves GBW EC 400 A


Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	56	52	52	47	43	40	35	27
L_{WA}	Inlet side	dB(A)	68	53	62	67	60	58	55	48
L_{WA}	Outlet side	dB(A)	71	61	62	64	67	62	57	48



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	1200	4050	210	0.93	36	0.19
8	990	3300	120	0.52	32	0.13
6	710	2340	50	0.22	25	0.08
4	430	1420	20	0.09	18	0.05

Performance curves GBW EC 400 B


Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	57	46	54	49	48	46	43	39
L_{WA}	Inlet side	dB(A)	72	53	64	65	66	67	59	53
L_{WA}	Outlet side	dB(A)	76	56	67	70	71	70	62	55



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	1500	5160	395	1.75	37	0.28
8	1250	4300	245	1.08	34	0.21
6	930	3200	120	0.52	29	0.13
4	710	2440	65	0.28	25	0.09

Performance curves GBW EC 400 T120


Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	60	41	38	36	37	35	32	24
L_{WA}	Inlet side	dB(A)	73	56	58	61	66	67	61	50
L_{WA}	Outlet side	dB(A)	75	62	63	65	71	70	77	53



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	1320	4730	280	1,24	43	0.21
8	1100	3950	170	0.80	39	0.15
6	820	2950	75	0.44	33	0.09
4	530	1880	30	0.30	23	0.06

Performance curves GBD EC 400 T120

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	63	44	41	39	40	38	35	27
L_{WA}	Inlet side	dB(A)	76	59	61	64	69	70	64	53
L_{WA}	Outlet side	dB(A)	78	65	66	68	74	73	70	57



	Free blowing					
Voltage V	**n** min⁻¹	**V̇** m³/h	**P** W	**I** A	**Lp** dB(A)	**SFP** kW/m³/s
10	1500	5410	410	1,00	46	0,27
8	1260	4550	260	0,60	42	0,21
6	950	3370	130	0,40	36	0,14
4	630	2220	60	0,20	28	0,10

Power control

Continuously variable speed control with internal (delivery) or external potentiometer or continuously variable speed regulation with universal control system (see table).
Performance levels are shown in the performance curve as an example.

Noise

The total level and range are specified above the performance diagram for:
- ☐ Case-radiated sound power
- ☐ Inlet side sound power
- ☐ Outlet side sound power

The case-radiated noise as sound pressure at 4 m (free field conditions) is also specified in the type table and the table below the performance curve.

Accessories for both series

Vibration dampers for indoor installation. 1 set = 4 pcs.
SDD-U Ref. no. 05627

Wall bracket for wall installation.
GB-WK 400 Ref. no. 05626

Weather protection grille for outlet-side coverage.
GB-WSG 400 Ref. no. 05639

Weather protection cover for protected outdoor installation.
GB-WSD 400 Ref. no. 05748

Special accessories

☐ **for GB EC series**
Condensate tray with drain connectors (central) for duct/hose connection.
GB-KW 400 Ref. no. 05644
(a condensate tray with condensate drain is included in delivery for GB EC T120).

☐ **for GB EC T120 series**
Rain drain for outdoor installation (Hole in casing base already provided).
GB-RA Ref. no. 09418

References	**Page**
Universal control system, electronic controllers, Speed potentiometer	615 ff.