
MV 100 – Single level



Dimensions MV 100



Dim. in mm MV 100 B, *MV 100 A

High pressure performance and high volume output with space-saving dimensions.
Specifically designed for direct insertion in duct systems. Various applications in commercial, industrial and residential areas.

Special features
- ▢ Low space requirement and installation costs due to linear throughflow.
- ▢ No need for elaborate deflectors.
- ▢ Connectors on inlet and outlet side correspond to standard duct Ø.
- ▢ Comes with two performance levels; 100% speed-controllable as standard.
- ▢ Can be used in any position.
- ▢ Long-life ball bearings, designed for 30000 operating hours.
- ▢ Problem-free maintenance and cleaning without dismantling the duct system due to the removable fan unit.
- ▢ Fan unit with terminal box can be rotated into any position.
- ▢ Integrated mounting bracket for easy installation to walls and ceilings.

Casing
The fan unit can be removed from the duct casing with integrated mounting bracket by loosening the clamp. All components are made of impact-resistant and corrosion-resistant plastic. Colour: Light grey.

Power control
With two performance levels as standard using an external operating switch MVB (accessories). Also with continuously variable control through electronic controller or five-step transformer.

Motor
Enclosed, ball bearing mounted motor with humidity protection, insulation class F, for continuous operation, maintenance-free.

Motor protection
Through thermal overload protection in the winding.

Noise
The total level and range are specified above the performance diagram for
- ▢ case-radiated sound power.
- ▢ Inlet/outlet side sound power in dB(A).
- ▢ The case-radiated noise and inlet/outlet side air noise as sound pressure at 1 m (free field conditions) are also specified in the type table.

Impeller
Optimised for high pressure performance and volume output, made of high-quality plastic.


Electrical connection
Spacious terminal box (IP44) on outside of casing; can be rotated into any position.

Installation
No restrictions in any position (horizontal, vertical, diagonal) through corresponding installation for supply or extract ventilation. Installation in duct system, preferably away from the room to be ventilated for less noise.

MV-MZ 100 B – Two level



Dimensions MV-MZ 100 B



Dim. in mm


Double pressure **Installation kit MV-MZ**

Description
Installation kit for arranging two MV fans in series. The pressure performance is approximately doubled through series operation. Scope of delivery: base plate (1 pc.), sleeve (1 pc.).


Electrical connection
A coupling relay must be provided according to the wiring diagram for controlling the two fans at two performance levels via one operating switch MVB (accessories) or one on-site changeover switch.
The high performance level must be connected when using speed controllers.

Installation
No restrictions in any position (horizontal, vertical, diagonal) through corresponding installation for supply or extract ventilation. Installation in duct system, preferably away from the room to be ventilated for less noise.

MV-MP 100 B – Parallel



Dimensions MV-MP 100 B



Dim. in mm

Double volume **Installation kit MV-MP**

Description
Installation kit for arranging two MV fans in parallel. The volume output doubles during parallel operation (joint control). Scope of delivery: mounting rails (2 pcs.), rectangular duct connection plates (2 pcs.).


Power control/Connection
A coupling relay must be provided according to the wiring diagram for controlling the two fans at two performance levels via one operating switch MVB (accessories) or one on-site changeover switch.
The high performance level must be connected when using speed controllers.
Each fan can also be individually controlled and connected to the second fan if necessary. In order to prevent backflow in this case, two duct shutters (type RSK, accessories) must be provided on the outlet side.

Type	Ref. no.	Connection Ø	Flow rate min./max.	Speed min./max.	Sound pres. lev at 1m: Case radiation	Sound pres. lev at 1m: Air noise min./max.	Power consum. min/max.	Current consum. min/max.	Wiring diagram	Max. air flow temp.	Wgt net aprx.	Transformer speed controller 5-step: Type	Transformer speed controller 5-step: Ref. no.	Electronic* speed controller, cont. variable flush/ surf-mount.: Type	Electronic* speed controller, cont. variable flush/ surf-mount.: Ref. no.
		mm	V̇ m³/h	min⁻¹	dB (A)	dB (A)	W	A	No.	+ °C	kg				
Single-phase alternating current, 230 V, 50 Hz, Capacitor motor, IP44															
MV 100 A	06050	100	150/190	2070/2620	34/38	45/50	12/15	0.05/0.07	844.1	60	1.2	**TSW 0.3**	03608	**ESU1/ESA1**	00236/00238
MV 100 B	06051	100	170/240	1590/2170	32/38	46/52	20/23	0.09/0.11	844.1	60	1.7	**TSW 0.3**	03608	**ESU1/ESA1**	00236/00238
Double pressure **Two level fan unit, 230 V, 50 Hz, Capacitor motor, IP44**															
MV-MZ 100 B	06078	100	170/240	1590/2170	37/43	49/55	40/46	0.18/0.22	845.1	60	4.5	**TSW 0.3**	03608	**ESU1/ESA1**	00236/00238
Double volume **Parallel twin unit, 230 V, 50 Hz, Capacitor motor, IP44**															
MV-MP 100 B	06085	–	340/480	1590/2170	35/41	49/55	40/46	0.18/0.22	845.1	60	5.7	**TSW 0.3**	03608	**ESU1/ESA1**	00236/00238

* Transformer control units must be provided in noise-relevant cases. Electronic phase angle control can cause disturbing magnetisation humming.


Performance curves MV 100 A – Single level

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	46	24	31	38	44	32	30	23
L_{WA}	Inlet side	dB(A)	58	27	46	51	54	52	44	33
L_{WA}	Outlet side	dB(A)	58	30	48	52	56	49	45	33




Performance curves MV 100 B – Single level

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	46	30	37	41	42	35	28	23
L_{WA}	Inlet side	dB(A)	60	34	52	54	52	55	42	33
L_{WA}	Outlet side	dB(A)	60	36	54	55	54	52	44	33




Performance curves MV-MZ 100 B – Two level

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	51	37	42	46	47	43	33	25
L_{WA}	Inlet side	dB(A)	63	40	56	58	55	57	47	36
L_{WA}	Outlet side	dB(A)	63	43	57	59	57	54	49	36



Performance curves MV-MP 100 B – Parallel

Frequency		Hz	Tot.	125	250	500	1k	2k	4k	8k
L_{WA}	Radiation	dB(A)	49	33	40	44	45	38	31	26
L_{WA}	Inlet side	dB(A)	63	37	55	57	55	58	45	36
L_{WA}	Outlet side	dB(A)	63	39	57	58	57	55	47	36



Accessories for MV and MV-MZ

Flexible connecting sleeve
FM 100 Ref. no. 01681
Includes 2 hose clamps; for installation between fan and duct system. Prevents structure-borne noise transmission and bridges installation tolerances.
2 pcs required for inlet and outlet side application.




External wall shutter
VK 100 Ref. no. 00757
Automatic overpressure shutter for external wall connection of air outlet opening. Made of white plastic.



External wall cover grille
G 100 Ref. no. 00796
For covering and insertion in round ventilation openings. Made of break-resistant, white plastic.



Protection grille
MVS 100 Ref. no. 06071
For inlet and outlet side installation on fan.



Flexible cross talk silencer
FSD 100 Ref. no. 00676
Made of aluminium pipe with double-sided plug-in connectors. Sound insulation lining 50 mm thick, installation length 1 m.



Air filter box
LFBR 100 Coarse 70%* 08576
Large-surface, installation in round duct system.



Electric heating element
EHR-R 0.4/100 0.4 kW No. 08708
In duct casing made of galvanised steel sheet.

Warm water heating element
WHR 100 Ref. no. 09479
For installation in duct system.

Accessories for all types

Duct shutter
RSKK 100 Ref. no. 05106
Automatic, made of plastic.
For installation in pipeline.



Operating switch 0-1-2
MVB Ref. no. 06091
With functions On/Off, Low and high speed.



Transformer speed controller
TSW See type table
Five-step, for surface installation.

Electronic speed controller
ESU/ESA See type table
For flush/surface installation.



Electronic turn-off delay switch
ZNE Ref. no. 00342
With continuously variable turn-off delay periods.



* See product page for detailed description