
Flange connection plate

FAP



Flange connection plate FAP
Made of galvanised steel sheet. This allows the connection of the duct system and accessories to the roof fans DV EC if no base silencer SSD is used.

Type	FAP 200	FAP 250	FAP 400
Ref. no.	08382	08383	08384
☐ A mm	430	550	635
☐ B mm	330	450	535
Ø D mm	200	250	400
Ø LK mm	259	286	438
M	M 6	M 6	M 8
Gewicht kg	1.8	3.0	3.3

Flange, flanged flex. connector

FR



STS



Compatible with roof fan:					
DV EC 200		DV EC 250		DV EC 400	
Type	Ref. no.	**Type**	Ref. no.	**Type**	Ref. no.
Flange connection plate – Required for duct-pipe connection					
FAP 200	08382	**FAP 250**	08383	**FAP 400**	08384
Counterflange					
DFR 200	01201	**FR 250**	01203	**FR 400**	01206
Flanged flexible connector					
DSTS 200	01218	**STS 250**	01220	**STS 400**	01223

See product pages for detailed description.

Flat roof base

Base silencer

FDS



SSD



Compatible with roof fan:					
DV EC 200		DV EC 250		DV EC 400	
Type	Ref. no.	**Type**	Ref. no.	**Type**	Ref. no.
Flat roof base – With swing-action device for easy inspection					
FDS 200	01378	**FDS 250**	01379	**FDS 400**	01380
Base silencer – With swing-action device for easy inspection					
SSD 200	05290	**SSD 250**	05292	**SSD 400**	05291

See product pages for detailed description.

Fire protection

ELS-D



Z-41.3-368

Fire protection ceiling seal ELS-D to prevent spread of fire to other floors. Installation in main ventilation pipe according to DIN 18017 K90. Maintenance-free. For ventilation or mixed (even with combustible pipes) installation shafts which only require cladding with 12.5 mm plasterboard. All other parts (disc valves etc.) without fire resistance classification. Branch and connection pipes also available in Aluflex pipe. Shutter elements KAK are available to prevent the backflow of cold smoke (see left page or page 597).

ND mm main pipe	100	125	140	160	180	200
Type	ELS-D 100	ELS-D 125	ELS-D 140	ELS-D 160	ELS-D 180	ELS-D 200
Ref. no.	00270	00185	00186	00187	00188	00271

Control system

ZLS-IF



ZLS-ZU 31



Interface
Interface for commissioning or controlling the fan in combination with a PC/laptop. Incl. mains adapter, adapter cable and software.
ZLS-IF Ref. no. 08391

Electronic timer module with day and night switchover
Allows the parallel operation of max. 31 DV EC roof fans. The rocker switch is used to enable the DV EC fans. The day and night switchover takes place via the settings in the display.
Incl. main switch. 230 V, 50 Hz.
ZLS-ZU 31 Ref. no. 08388

Accessory details	Page
Roof install. accessories	559 f.
Ventilation grilles	561 ff.
Extract air elements	574 ff.
Intake air elements	586 ff.
Fire protection systems	590 ff.
– Ceiling seal	596 ff.
Universal control systems, electronic controllers, speed potentiometer	613 ff.

EUR EC



PU / PA



Universal control system
For the continuously variable control or regulation of single and three-phase EC fans with a setpoint of 0–10 V DC:
EUR EC Ref. no. 01347

Speed potentiometer
For the direct control/setpoint setting of EC fans with a potentiometer input.
PU 10 (UP) Ref. no. 01734

PA 10 (AP) Ref. no. 01735