## FGR



### Round facade grille

For the flush coverage of ventilation openings on the facade. Applicable for round intake and exhaust air ducts. Two holes in the duct connector enable secure fastening with screws to be provided by the customer. Stable aluminium construction. Fixed blades with stainless steel wire mesh grille behind them, mesh size 10 x 10 mm.

### Product range

| Type | Ref. no. | Weight in grammes |
|---|---|---|
| **FGR 80** | 40195 | 100 |
| **FGR 100** | 40196 | 150 |
| **FGR 125** | 40197 | 180 |
| **FGR 160** | 40198 | 300 |
| **FGR 200** | 40199 | 400 |
| **FGR 250** | 40181 | 900 |
| **FGR 315** | 40182 | 1600 |

| Type | Dimensions in mm | | | |
|---|---|---|---|---|
| | A | B | C | D |
| **FGR 80** | 98 | 81 | 12 | 4 |
| **FGR 100** | 124 | 99 | 17 | 3 |
| **FGR 125** | 151 | 125 | 17 | 3 |
| **FGR 160** | 182 | 160 | 14 | 4 |
| **FGR 200** | 224 | 199 | 16 | 4 |
| **FGR 250** | 275 | 250 | 15 | 5 |
| **FGR 315** | 345 | 314 | 14 | 7 |

## LG



### Ventilation grille LG

With diagonally positioned blades for covering round ventilation openings Ø 80, 100, 125 and 160 mm.

- ▢ High-quality and attractively designed covering.
- ▢ Diagonally positioned blades act as a sight screen (with appropriate installation).
- ▢ Made of corrosion-resistant die-cast aluminium, powder-coated, colour: white. LGK 80 made of high-quality, break-resistant plastic, colour: white.
- ▢ Simple installation in ducts due to rear plug-in connectors with clamp springs and sealing strip.

### Product range

| Type | Ref. no. | Weight in grammes |
|---|---|---|
| **LGK 80*** | 00259 | 120 |
| **LGM 100** | 00254 | 300 |
| **LGM 125** | 00258 | 450 |
| **LGM 160** | 00261 | 750 |

* Made of plastic.

| Type | Dimensions in mm | | | |
|---|---|---|---|---|
| | A | B | C | D |
| **LGK 80** | 135 | 105 | 14 | 80 |
| **LGM 100** | 155 | 127 | 16 | 95 |
| **LGM 125** | 195 | 150 | 25 | 120 |
| **LGM 160** | 252 | 190 | 25 | 155 |

## LTG



### Door ventilation grille LTG


Fixed overflow grille for installation in door leaves.

- ▢ Pleasant and unobtrusive design. Made of high-quality break-resistant plastic, in light grey or brown.
- ▢ With wide circumferential edge and diagonally positioned blades, sight screening. Only 3 mm high.
- ▢ Two-part, telescopic. Installation: Insert both sides of each element into the recess and tighten against each other using the screws supplied.

### Product range


| Type | Ref. no. | Colour |
|---|---|---|
| **LTGW** | 00246 | White |
| **LTGB** | 00247 | Brown |

## Dimensions FGR





Dim. in mm – see table

## Dimensions LG





Dim. in mm – see table

## Dimensions LTG





Dim. in mm  Door leaf depth min. 30 mm

## Pressure loss FGR




## Pressure loss LG




## Pressure loss LTG

