
KWL EC 70




Efficiency class

A+ KWL EC 70

With second room connection



Surface mounting



Compact ventilation unit with heat recovery for wall mounting – on or in the exterior wall. In addition to the room in which it is installed, another room can also be ventilated or deaerated. KWL EC 70 offers an efficient solution for ensuring comfortable indoor air quality while maintaining high energy efficiency. The space-saving design allows flexible use in many living and usage situations. Ideal for smaller residential units such as flats, hotel rooms, retirement homes, residential homes or student accommodation. Equipped with economical EC fans, highly efficient cross-counterflow or enthalpy heat exchangers and user-friendly operation.

Housing
- Universal housing concept. Unit made of highly insulating EPP. Maintenance-friendly access to filters via hinged inner panel. Easy-to-maintain filter access via hinged inner cover. Surface mounting: easy retrofitting during renovation. Partially integrated into wall: discreet appearance, connection to second room possible (supply/exhaust air).

Heat exchanger
- Large-area cross-counterflow heat exchanger made of plastic, with a heat recovery rate of up to 85 %.
- Type 'ET' is equipped with a highly efficient enthalpy heat exchanger for additional moisture recovery.

Fans
- Two quiet, high-performance centrifugal fans with energy-saving EC motors ensure air supply and extraction.

Condensate drainage
- If condensate forms due to air conditions, it is reliably drained via the facade cover or the soffit element.

Air filter
- Clean outdoor air supply via ISO Coarse 65% (G4) filter or alternatively through ISO ePM$_1$ 60% (F7) or activated carbon filter. The extract air side is equipped with an ISO Coarse 65% (G4) filter before the heat exchanger. Easy filter maintenance without opening the unit is possible.


Frost protection for the heat exchanger
- The standard frost monitoring system automatically adjusts the supply air volume.

Control
- The casing features a discreet membrane keypad with 5 ventilation settings.
- Operating modes: Pure supply air / Pure extract air / Heat recovery.
- After a pre-set time interval, the user is reminded of the filter replacement via an optical signal.
- The unit features an integrated humidity sensor for demand-based automatic operation. Additional air quality sensors (VOC, CO_2) are available for integration into the device or external variants for installation in the room.

Electrical connection
- Fixed line connection via an NYM cable 3 x 1.5 mm^2.

Commissioning
- Easy configuration of the KWL EC 70 using the setup tool (PC/laptop) via USB connection.

Dimensions KWL EC 70



Dimensions in mm


- Commissioning and parameter entry (e.g. filter change, minimum fan speed) are easily carried out via the programme interface with context-sensitive help texts.
- Configurations can be saved on a PC/laptop and reloaded as required.
- The configuration can be saved and transferred to other devices. This makes commissioning in larger properties particularly easy.
- The set values can be secured in the software using a PIN.

Replacement air filters
– 2 pc. ISO Coarse 65% (G4)
ELF-KWL EC 70/2x Coarse 65%
Ref. no. 40849
– 1 pc. ISO ePM$_1$ 60% (F7)
ELF-KWL EC 70/ePM1 60%
Ref. no. 40868
– 1 pc. Activated carbon filter
Ref. no. 40869


Reference
Enthalpy heat exchanger (accessories) for retrofitting:
KWL-ET 70 Ref. no. 40957

Technical data	With cross-counterflow heat exchanger Type	Ref. no.	With enthalpy heat exchanger Type	Ref. no.
	KWL EC 70	40787	**KWL EC 70 ET**	40788
Heating capacity	87 %		85 %	
Levels	❶	❷ ❸ ❹ ❺		
Ventilation levels V̇ m³/h	30	40 50 60 70		
Sound power L_{WA} dB(A)	33	38 40 43 45		
Sound pressure L_{PA} dB(A) at 3 m	15	20 22 25 27		
Rated output W	5	7 10 14 19		
Rated current A	0,36			
Max. electrical input power W	50			
Standard sound level difference $D_{n,e,w}$ dB(A)	45			
Temperature operating range	–20 °C to + 40 °C			
Voltage/Frequency	1~, 230 V, 50 Hz			
Wiring diagram no.	1535			
Weight approx. kg	9			


Performance curves KWL EC 70








Wall installation element
KWL 70 WEE Ref. no. 40852
Wall installation element made of EPS, incl. 2 wall installation sleeves (500 mm) with protective cover, as well as rectangular protective cover for the unit insert.





Adaptor
KWL 70 PS Ref. no. 40853
For completing the wall installation element with a full wall opening.

Flexible ventilation duct
FRS-R 75 Ref. no. 02913
Corrugated plastic pipe made of PE-HD in quality-assured quality. Outer diameter: 75 mm, inner diameter: 63 mm. For volume flows up to 30 m³/h. Packaging unit: 1 bundle of 50 running metres.







Seal ring for ventilation duct 75 mm
FRS-DR 75 Ref. no. 02916
Seal ring for FRS-R 75. Required at every connection point. Set of 10 pieces.


Ceiling/wall box DN 125
FRS-DWK 2-75/125 No. 03857
Ceiling/wall box for max. 2 round ducts FRS-R 75. For connection of supply/extract air valves DN 125. Height marks can be shortened to fit. Includes 1 blind cover DN 75 and DN 125. Integr. mounting clips, duct mounting brackets (4 pcs.), made of impact-resistant polypropylene.





Facade panel
KWL 70 FB-E Ref. no. 40857
Stainless steel panel for the external facade.
KWL 70 FB-B Ref. no. 40858
With additional coating for environments with high levels of air pollution or high salt concentrations in the air (near the coast).
KWL 70 FB-W Ref. no. 40859
With white coating.





Design ventilation valve
DLV 125 Ref. no. 03049
With integrated filter for supply and exhaust air operation, DN 125, adjustable.
DLV 125 black Ref. no. 40786

Second room connection
KWL 70 ZAS Ref. no. 40854
For the connection of an additional room. Set consists of:
2 × connectors for FRS-R75
4 × bracket FRS-FK
1 × Closing cover for supply or exhaust air side
2 × sealing ring

Surface-mounted housing
KWL 70 AG Ref. no. 40865
For installing the KWL EC 70 on the wall. Incl. mounting material for the unit. Material: Plastic

Wall installation sleeve
Length 500 mm
KWL 70 WH Ref. no. 40855
Set consisting of 2 pieces. Diameter 110 mm. Material: PPS. Includes 4 building protection covers and 2 mounting templates for hygienic closure during the shell construction phase.
Length 800 mm
KWL 70 WH-L Ref. no. 40856

Installation kit Soffit
KWL 70 LE-RP Ref. no. 40860
Soffit channel with plaster frame and adapter. Made of EPP, fire protection class B1. Can be installed on the left or right side of the window.

Stainless steel soffit grille
KWL 70 LG-E Ref. no. 40861
External grille including stainless steel condensate drain and seal.
KWL 70 LG-B Ref. no. 40862
For use in environments with high levels of air pollution or high salt concentrations in the air (near the coast).
With white coating
KWL 70 LG-W Ref. no. 40863
Soffit grille with white coating.

Insect screen
KWL 70 ISL Ref. no. 40864
Made of stainless steel. For Installation kit Soffit (KWL 70 LE-RP). Suitable for retrofitting.

Room sensors
AIR1/KWL-VOC 0-10V No. 20250
AIR1/KWL-CO2 0-10V No. 20251
AIR1/KWL-FTF 0-10V No. 20252
For detecting the CO_2, mixed gas (VOC) concentration or relative room air humidity.
Dim. mm (W x H x D) 85 x 85 x 27

Internal sensors
KWL 70 VOC-I Ref. no. 40867
KWL 70 CO2-I Ref. no. 40866
Internal sensor for detecting the CO_2, or mixed gas (VOC) concentration.